

PROFESSIONAL STANDING SPEAKER

EMOTION SERIES

중,대규모의 회의실에서 부터 강당까지 뛰어난 주파수 대역의 특성으로 다양한 용도의 어플리케이션을 소화할 수 있습니다. 힘있는 저음의 구현 및 높은 음역의 명료도 또한 겸비하여, 다양한 장르의 음악 표현이 가능합니다.



EMOTION 8

EMOTION 28

EMOTION 10M

EMOTION 12M

EMOTION 12

EMOTION 15

EMOTION 157

FEATURES

Model Characteristic	EMOTION 8	EMOTION 28	EMOTION 10M
- System type	8" + 1" 2-WAY SYSTEM	Dual 8" + 1" 2-WAY SYSTEM	10" + 1" 2-WAY SYSTEM COXIAL TYPE
- Power Handling	RMS 200W / PROGRAM 400W	RMS 400W / PROGRAM 800W	RMS 300W / PROGRAM 600W
- Impedance	8ohm	8ohm	8ohm
- SPL(1W/1M)	94dB	97dB	97dB
- Frequency Range	65Hz~18KHz	65Hz~20KHz	50Hz~20KHz
- Coverage(H/V)	60° / 40°	90° / 60°	90° / 90°
Driver Components			
- HF	1" Compression Driver	1" Compression Driver	1" Compression Driver
- LF	8" Driver	8" Driver	10" Driver
- X-Over Frequency	2.7 KHz	2.2 KHz	2.7 KHz
- Enclosure	Birch plywood made	Birch plywood made	Birch plywood made
- Dimensions(WxHxD)	250 x 422 x 285mm	250 x 612 x 320mm	315 x 550 x 240mm
- Weight	11kg	16kg	14kg

Model Characteristic	EMOTION 12M	EMOTION 12	EMOTION 15 (EMOTION 157)
- System type	12" + 1" 2-WAY SYSTEM	12" + 1" 2-WAY SYSTEM	15" + 1" 2-WAY SYSTEM
- Power Handling	RMS 400W / PROGRAM 800W	RMS 400W / PROGRAM 800W	RMS 500W (700W) / PROGRAM 1000W (1400W)
- Impedance	8ohm	8ohm	8ohm
- SPL(1W/1M)	96dB	96dB	97dB (99dB)
- Frequency Range	40Hz~20KHz	45Hz~18KHz	40Hz~19KHz (30Hz~19KHz)
- Coverage(H/V)	80° / 80°	80° / 50°	70° / 40°
Driver Components			
- HF	Coaxial 12" Driver	1" Compression Driver	1" Compression Driver
- LF		12" Driver	15" Driver
- X-Over Frequency	2.0 KHz	2.2 KHz	2.0 KHz
- Enclosure	Birch plywood made	Birch plywood made	Birch plywood made
- Dimensions(WxHxD)	500 x 373 x 450mm	368 x 597 x 345mm	452 x 725 x 390mm
- Weight	24kg	21kg	34kg (35kg)