

PROFESSIONAL CEILING SPEAKER



LCL-6T



LCL-8T

LCL SERIES

건축물 실내의 천정에 설치할 수 있도록 원형의 구조와 POLYPROPYLENE 재질로 구성되어 있습니다.
2웨이 스피커를 내장하여 명료한 음성 전달뿐 아니라, BGM등 다용도로 사용할 수 있는 넓은 주파수 특성을 지니고,
다수의 스피커 사용시, 하나의 앰프로 사용이 가능하도록 하이임피던스 매칭트랜스포머를 내장한 제품입니다.

FEATURES

Model Characteristic	LCL-6T
- System Type	6.5" 2-WAY Coaxial type
- Power Handling	45W RMS (8ohm)
- SPL(1W/1M)	89dB
- Nominal diameter	165 mm. 6.5inch
- Frequency Range	45Hz~20KHz
- Coverage(H/V)	90°
- Transformer line	100V
- Connectors	Spring-loaded terminals
- Driver components	Coaxial 6" Driver
- Enclosure	ABS
- Hall size	φ 210
- Dimensions(WxD)	φ 240 x 140mm
- Weight	2kg

Model Characteristic	LCL-8T
- System Type	8" 2-WAY Coaxial type
- Power Handling	55W RMS (8ohm)
- SPL(1W/1M)	91dB
- Nominal diameter	200 mm. 8inch
- Frequency Range	40Hz~20KHz
- Coverage(H/V)	90°
- Transformer line	100V
- Connectors	Spring-loaded terminals
- Driver components	Coaxial 8" Driver
- Enclosure	ABS
- Hall size	φ 250 mm
- Dimensions(WxD)	φ 280 x 180mm
- Weight	3kg